

DEF2CLH050DA3B

“ # ” indicates a package specification code.


Recommended

Flow OK

Complies with RoHS

< List of part numbers with package codes >
DEF2CLH050DA3B

Shape



Lead Code	Coating Extension e	ø d
A3	Up to the end of crimp	0.6±0.05

L size or outer diameter D (mm)	7.0 mm max.
Lead spacing F	7.5 ± 1.0mm
Product thickness T	6.0mm max.
Lead diameter d	0.6 ± 0.05mm
Paint dripping e	Up to the end of crimp

Notes

For LCD Backlight Inverters only

References

Packaging	Specifications	Minimum quantity
	Packing in bulk	250

Specifications

Capacitance	5.0pF ± 0.5pF
Rated voltage	6300Vdc(p-p)
Temperature characteristics (complied standard)	CH(JIS)
Temperature coefficient	0 ± 60ppm/
Temperature range of temperature characteristics	20 to 85
Operating temperature range	-25 to 105

Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.